

CHASSIS

chassis/**xxHP**

MPPI chassis

_MAIN FEATURES

- 4U height
- 3U 160mm depth cards
- 0.5U top and bottom spaces for cooling and connections
- 28HP, 42HP and 84 HP versions
- Power supply included
- Optional 0.5U air convection system



_PRODUCT SPECIFICATIONS

	chassis/28HP	chassis/42HP	chassis/84HP
Height	4U height (177 mm) 3U 160mm depth cards 0.5U top and bottom for cooling and connections		
Width	28HP (177.62 mm)	42HP (248.74 mm)	84HP (462.10 mm)
Depth	315.5 mm		
Number of modules	7 slots (SOM/E + 6 modules)	10 slots (SOM/E + 9 modules)	21 slots (SOM/E + 20 modules)
Internal power supply	AC input (100-240 VAC) 2.1 A	AC input (100-240 VAC) 3 A	AC input (100-240 VAC) 5.9 A
Auxiliary external power supply	6 VDC, dual banana plug		Not available
Convection	Optimum air flux system. Passive (standard) Forced air convection (optional). 0.5U multi axial fans tray		

_ORDERING INFORMATION

This product is commercialized by Eblana Photonics:

sales@eblanaphotonics.com

+353 1 675 3220

Part number:

chassis/xxHP-a

xx:

28 (28HP)

42 (42HP)

84 (84HP)

a:

p (passive cooling)

f (forced cooling, multi axial fan 0.5U top tray inside chassis)

You can acquire this product individually for OEM applications or as part of a MPPI system (see MPPI Brochure for further information and system configuration)

COMMERCIALIZED BY



eblanaphotonics

| **a** West Pier Business Campus, 3, Old Dunleary Rd, Dún Laoghaire, Co.
Dublin, A96 A621, Ireland
| **p** +353 1 675 3220
| **e** sales@eblanaphotonics.com
| **w** eblanaphotonics.com

_v1.1 datasheet

chassis/**xxHP**

All product specifications are subject to change without prior notice



luzwavelabs